

GET Electric

22kW Fast Charger

Specification	Model	GC22-SB-G3
AC Nominal Input	Phases/Lines	3 phase + netural+ PE
	Voltage	415V±10%
	Frequency	50Hz
AC Nominal Output	Voltage	415V±10%
	Current	32A
	Power	22KW
Structure Design	Housing Material	Galvanized steel
	Front Panel	Tempered glass
	Installation Method	Wall-mount/Floor-stand/Recessed
	Wall-mount Bracket	Yes
	Charging Outlet	One charging plug (Type 2)
	Cable Length	4M
	LED Indicator	Green/Yellow/Red color for different status
	LCD Screen	Color Touch
	RFID Function	Yes
	RFID Card	Mifare card
	Energy Meter	MID certified
	RCD	Type A+ 6mA DC
Environmental Index	Operating Temperature	- 30~ + 50℃
	Working Humidity	5%~95% without condensation
	Working Altitude	<2000M
	Protection Grade	IP54
	Application Site	Indoor/Outdoor
	Cooling Method	Natural cooling
Security Protection	Multiple Protection	Over/Under voltage protection,Overload protection,Short circuit protection,Current leakage protection,Grounding protection,Surge protection,Over/Under temperature protection
	MTBF	100,000 hours
	Safety Standard	IEC 61851-1:2017,IEC 62196-2:2016
	Warranty	2 Years
Package Information	Product Dimension	452*295*148MM
	Package Dimension	560*380*210MM
	Net Weight	10KG
	Gross Weight	12KG
	External Packing	Carton
Communication	Network	Ethernet/3G/4G communication
	Communication Protocol	OCPP1.6(JSON)
	Floor-stand Mount	Optional